

Die optimalen Felgenbreiten sind Fett hervorgehoben.

Reifengröße	zulässige Felgenbreite				Reifenbreite	zulässige Felgenbreite			
2 ¼ x 16	1.2	1.5	1.6		80/90	1.6	1.85	2.15	
2 ½ x 16	1.5	1.6	1.85		90/90	1.85	2.15	2.5	
2 ¾ x 16	1.5	1.6	1.85		100/90	2.15	2.5	2.75	
2 ¼ x 17	1.5	1.6			110/90	2.15	2.5	2.75	3
2 ½ x 17	1.5	1.6	1.85		120/90	2.5	2.75	3	
2 ¾ x 17	1.5	1.6	1.85		130/90	2.5	2.75	3	3.5
2.25 x 17	1.5	1.6			140/90	2.75	3	3.5	3.75
2.50 x 17	1.5	1.6	1.85		150/90	3	3.5	3.75	4
2.50 x 18	1.5	1.6							
2.50 x 19	1.5	1.6	1.85		100/80	2.15	2.5	2.75	
2.50 x 21	1.5	1.6	1.85		110/80	2.15	2.5	2.75	3
2.75 x 16	1.5	1.6	1.85		120/80	2.5	2.75	3	
2.75 x 17	1.5	1.6	1.85		130/80	2.5	2.75	3	3.5
2.75 x 18	1.5	1.6	1.85		140/80	2.75	3	3.5	3.75
2.75 x 21	1.6	1.85	2.15		150/80	3	3.5	3.75	4
3.00 x 17	1.6	1.85	2.15						
3.00 x 18	1.6	1.85	2.15		110/70	2.75	3	3.5	
3.00 x 19	1.6	1.85	2.15		120/70	3	3.5	3.75	
3.00 x 21	1.6	1.85	2.15		130/70	3.5	3.75	4	
3.25 x 16	1.85	2.15	2.5		140/70	3.5	3.75	4	4.5
3.25 x 18	1.85	2.15	2.5		150/70	3.5	3.75	4	4.5
3.25 x 19	1.85	2.15	2.5		160/70	4.25	4.5	5	
3.25 x 21	1.6	1.85	2.15		180/70	5	5.5		
3.50 x 16	1.85	2.15	2.5		200/70	5.5	6	6.25	
3.50 x 18	1.85	2.15	2.5						
3.50 x 19	1.85	2.15	2.5		120/60	3	3.5	3.75	
3.60 x 19	1.85	2.15	2.5		130/60	3.5	3.75	4	
4.00 x 18	2.15	2.5	2.75		150/60	4	4.5		
4.10 x 18	2.15	2.5	2.75	3	160/60	4.25	4.5	5	
4.50 x 17	2.15	2.5	2.75	3	170/60	4	4.5	5	5.5
4.60 x 16	2.15	2.5	2.75	3					
4.60 x 17	2.15	2.5	2.75	3	180/55	5.5	6		
4.60 x 18	2.15	2.5	2.75	3					
5.10 x 17	2.5	2.75	3	3.5	190/50	5.5	6		

Alle Angaben ohne Gewähr

Alte und neue Felgenbezeichnungen

WM 0 = 2 = 1.50

WM 1 = 2 $\frac{1}{4}$ = 1.60

WM 2 = 2 $\frac{1}{2}$ = 1.85

WM 3 = 3 = 2.15

WM 4 = 4 = 2.50